

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Alto-Shaam	1000-BQ2/128	1000-BQ2/128	Full Size	13.46	-	\$300
Alto-Shaam	1000-BQ2/192	1000-BQ2/192	Full Size	11.89	-	\$300
Alto-Shaam	1000-BQ2/96	1000-BQ2/96	Full Size	15.05	-	\$300
Alto-Shaam	1000-UP	1000-UP	Full Size	18.25	-	\$300
Alto-Shaam	Hot Holding Cabinets	12.20MW	Full Size	10.92	12.20W	\$300
Alto-Shaam	1200-S	1200-S	1/2 Size	20	-	\$200
Alto-Shaam	1200-UP	1200-UP	Full Size	20	-	\$300
Alto-Shaam	Hot Holding Cabinets	20.20MW	Full Size	9.94	20.20W	\$300
Bevles/Bakers Pride/APW Wyott	CS82-CH8	CS82-CH8	Full Size	18.6	-	\$300
Bevles/Bakers Pride/APW Wyott	Climate Select	HCSS74W12	Full Size	20.0	HCSS74W12	\$300
Bevles/Bakers Pride/APW Wyott	Temper Select	HTSS74W12	Full Size	20.0	HTSS74P34 HTSS74W12A	\$300
California Cooking	Holding and Transport Cabinet	CCK1826-15-BC-IS	Full Size	13.4	-	\$300
Cambro	Camtherm Bulk Food Cabinet	CMBH1826L	1/2 Size	10.0	CMBH1826LF CMBH1826LC CMBH1826LTR	\$200
Cambro	Camtherm Bulk Food Cabinet	CMBH1826TSF	Full Size	11.8	CMBH1826TBF CMBH1826TSC CMBH1826TBC CMBH1826TTR	\$300
Cambro	Ultra Camcart	UPCH1600	Full Size	15.1	UPCH16002	\$300
Cambro	Hot Holding Ultra Pan Carrier	UPCH400	1/2 Size	15.1	UPCH4002 UPCHW400 UPCHW4002	\$200

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Cambro	Ultra Camcart	UPCH800	1/2 Size	15.1	UPCH8002 UPCHT800	\$200
Carter-Hoffmann	Banquet Cart	BB1824	1/2 Size	10.9	-	\$200
Carter-Hoffmann	Banquet Cart	BB1848	3/4 Size	10.9	BB40	\$250
Carter-Hoffmann	Banquet Cart	BB1864	Full Size	10.9	BB48	\$300
					BB64	
					BB72	
					BB90	
					BB96	
					BB96X	
					BB100	
					BB120	
					BB120X	
					BB150	
					BB150X	
BB200D						
BB1000						
BB1200						
PS96						
Carter-Hoffmann	Enduraheat Banquet Cart	BR96	Full Size	18.2	BR120 BR150 BR1000 BR1200	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Carter-Hoffmann	Heated Transport Cart	PH1800	3/4 Size	10.8	PH1220 PH1225 PH1230 PH1240 PH1425 PH1800 PH1810 ST1811	\$250
Carter-Hoffmann	Heated Transport Cart	PH181	1/2 Size	10.8	ST181 PH1200 PH1210 PH1215 PH1400 PH1410	\$200
Carter-Hoffmann	Heated Transport Cart	PH181 (120V)	Full Size	10.8	PH1250 PH1420 PH1430 PH1440 PH1450 PH1460 PH1825 PH1830 PH1850 PH1860	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Carter-Hoffmann	Heated Transport Cart	PH181 (208V)	Full Size	10.8	PH1250 PH1420 PH1430 PH1440 PH1450 PH1460 PH1825 PH1830 PH1850 PH1860	\$300
Cleveland	CONVOHOLD™ Insulated Heated Stainless Steel Banquet Cart	HCWH-20.20	Full Size	13.6	HCDH-20.20	\$300
Cres Cor	Insulated Heated Stainless Steel Banquet Cart	CCB-120A	Full Size	11.4	-	\$300
Cres Cor	Insulated Heated Stainless Steel Banquet Cart	CCB-150	Full Size	15.3	-	\$300
Cres Cor	Insulated Heated Stainless Steel Banquet Cart	EB-150	Full Size	15.2	EB-150S EB-150208 EB-15208S EB-150240 EB-150240S EB-150CAN EB-150CANS	\$300
Cres Cor	Insulated Heated Stainless Steel Banquet Cabinet	H137S96BC	Full Size	9.9	-	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Cres Cor	Insulated Aquatemp Holding Cabinet	H137UA12C**2K	Full Size	17.6	H137WUA12C**2K H1381834C**2K (*may have other alpha numeric characters within this location)	\$300
Cres Cor	Insulated Holding Cabinet	H137UA9CD	3/4 Size	15.0	H137UA9C	\$250
Cres Cor	Insulated Stainless Steel Aquatemp Holding Cabinet	H137WSUA12C	Full Size	12.4	H137SUA12C	\$300
Cres Cor	Insulated Stainless Steel Holding Cabinet	H137WSUA6CMD	1/2 Size	17.8	H137WSUA6CM H137SUA6CM H138WS1816CM H138S1816CM	\$200
Cres Cor	Insulated Holding Cabinet	H1381834C	Full Size	15.0	H138S1834C	\$300
Cres Cor	H161FUA11CM	H161FUA11CM	Full Size	19.5	-	\$300
Cres Cor	Insulated Half-Size Stainless Steel Holding Cabinets	H339188CBKC	Full Size	17.1	H339188CPBKC	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Cres Cor	Insulated Half-Size Stainless Steel Holding Cabinets	H339SS12188C	1/2 Size	17.1	H339SS188C H339SST188C H339SS12188C H339SST12188C H339SSUA8C H339SSTUA8C H339XSS188C H339XSS12188C H339XSSUA8C	\$200
Cres Cor	Insulated Holding Cabinet	H339SS1814C	1/2 Size	17.1	-	\$200
Cres Cor	Insulated Half-Size Stainless Steel AquaTemp System Cabinet	H339WSSUA8D	1/2 Size	16.9	-	\$200
Delfield	SAHPT2-GHSH	SAHPT2-GHSH	Full Size	18.4	-	\$300
Food Warming Equipment Company, Inc.	Banquet Cabinets	E720XL	Full Size	13.0	-	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Food Warming Equipment Company, Inc.	Handy Line Radiant Heat Load Design	HLC-1826-5 (120v 1000W)	1/2 Size	18.0	HLC-1826-4 HLC-1826-4A HLC-1826-4F HLC-1826-8 HLC-1826-8A HLC-1826-8F HLC-SL-1826-5 HLC-10 HLC-10S HLC-14 HLC-14S HLC-16 HLC-16-CHP (120V 1000W models only)	\$200

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Food Warming Equipment Company, Inc.	Handy Line Radiant Heat	HLC-5 (120 v 500W)	1/2 Size	16.0	HLC-7 HLC-8 HLC-8-CHP HLC-5H-15 HLC-5S HLC-7H-21 HLC-7S HLC-8H-24 HLC-8S HLC-1227-6 HLC-1717-5 HLC-1717-13 HLC-18 HLC-18S HLC-1826-4 HLC-1826-4A HLC-1826-4F HLC-1826-8 HLC-1826-8A HLC-1826-8F HLC-SL-1	\$200
Food Warming Equipment Company, Inc.	Hndy Line Radiant Heat Side Load Design	HLCSL-1826-8	1/2 Size	14.6	-	\$200
Food Warming Equipment Company, Inc.	Moisture-Temp Holding	MTU-12	Full Size	16.0	-	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Food Warming Equipment Company, Inc.	Mobile Humi-Temp Universal Servers	UHS-10	Full Size	14.5	-	\$300
Food Warming Equipment Company, Inc.	Mobile Humi-Temp Universal Servers	UHS-12	Full Size	14.4	-	\$300
Hot Food Boxes, Inc.	C-12UPM	C-12UPM	Full Size	19.6	-	\$300
InterMetro Industries Corporation	C5 6 Series, Full Height, 2000W, Stainless Steel, Reach-In, Glass Door Cabinets	C569-SDC-U	Full Size	17.4	C569-SDC-** C569-SFC-**	\$300
InterMetro Industries Corporation	C5 6 Series, Full Height, 2000W, Stainless Steel, Reach-In, Solid Door Cabinets	C569-SDS-U	Full Size	15.5	C569-SDS-** C569-SFS-**	\$300
InterMetro Industries Corporation	C5 6 Series, Full Height, 1440W, Stainless Steel, Reach-In Cabinets	C569L-SDC-U	Full Size	14.8	C569L-SDC-** C569L-SFC-** C569L-SDS-** C569L-SFS-**	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

List maintained by PG&E Food Service Technology Center (FSTC) - www.fishnick.com

NOTE: List subject to change without notice. Please check the FSTC website for latest version.

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
InterMetro Industries Corporation	C5 9 / 8 Series, Full Height, Stainless Steel, Reach-In, Glass Door Cabinets	C599-SDC-U	Full Size	19.0	C599-SDC-** C599-SFC-** C599L-SDC-** C599L-SFC-** C589-SDC-** C589-SFC-** C589L-SDC-** C589L-SFC-**	\$300
InterMetro Industries Corporation	C5 9 / 8 Series, Full Height, Stainless Steel, Reach-In, Solid Door Cabinets	C599-SDS-U	Full Size	18.2	C599-SDS-** C599-SFS-** C599L-SDS-** C599L-SFS-** C589-SDS-** C589-SFS-** C589L-SDS-** C589L-SFS-**	\$300
InterMetro Industries Corporation	C5 9 Series Controlled Humidity Cabinets	C599-SDS-UPDS	Full Size	19.2	C599-SDS-LPDS C599-SFS-UPFS C599-SFS-LPFS	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-120	Full Size	17.5	MBQ-120-QH	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-120D	Full Size	14.0	MBQ-120D-QH	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-144	Full Size	15.6	MBQ-144-QH	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-150D	Full Size	14.6	MBQ-150D-QH	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-180	Full Size	12.5	MBQ-180-QH	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-180D	Full Size	14.6	MBQ-180D-QH	\$300
InterMetro Industries Corporation	Heated Banquet Cabinet	MBQ-200D	Full Size	13.8	MBQ-200D-QH	\$300
InterMetro Industries Corporation	Top Mount Heated Banquet Cabinet	MBQT-180D	Full Size	15.3	MBQT-180DQH MBQT-180D-*****	\$300
McCall Refrigeration	4-4020H	4-4020H****	Full Size	12.5	1-1020H**** 2-2020H**** (may have model suffixes A, C, P or 01)	\$300
McCall Refrigeration	4-4045H	4-4045H****	Full Size	4.8	1-1045H**** 2-2045H**** (may have model suffixes A, C, P or 01)	\$300
Royalton Food Service Equipment	RHHC-1000-C4	RHHC-1000-C4	Full Size	18.8	-	\$300
Traulsen & Co., Inc.	AHF132-FHS	AHF132-FHS	Full Size	6.7	RHF132-FHS	\$300
Traulsen & Co., Inc.	AHF132-HHS	AHF132-HHS	Full Size	6.7	RHF132-HHS	\$300
Traulsen & Co., Inc.	AHF132W-FHS	AHF132W-FHS	Full Size	6.7	-	\$300
Traulsen & Co., Inc.	AHF132W-HHS	AHF132W-HHS	Full Size	6.7	-	\$300
Traulsen & Co., Inc.	AHF132WP-FHS	AHF132WP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF132WP-HHS	AHF132WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF232W-FHS	AHF232W-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF232W-HHS	AHF232W-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF232WP-FHS	AHF232WP-FHS	Full Size	6.8	-	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Traulsen & Co., Inc.	AHF232WP-HHS	AHF232WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF332W-FHS	AHF332W-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF332W-HHS	AHF332W-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF332WP-FHS	AHF332WP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AHF332WP-HHS	AHF332WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AIH132L-FHS	AIH132L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AIH132LP-FHS	AIH132LP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AIH232L-FHS	AIH232L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AIH232LP-FHS	AIH232LP-FHS	Full Size	6.3	-	\$300
Traulsen & Co., Inc.	AIH332L-FHS	AIH332L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	AIH332LP-FHS	AIH332LP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	G14300	G14300	Full Size	6.7	G14301	\$300
Traulsen & Co., Inc.	G14302P	G14302P	Full Size	6.8	G14303P G14304P G14305P	\$300
Traulsen & Co., Inc.	G14310	G14310	Full Size	6.7	G14311	\$300
Traulsen & Co., Inc.	G14312P	G14312P	Full Size	6.8	G14313P G14314P G14315P	\$300
Traulsen & Co., Inc.	G24300	G24300	Full Size	8.3	G24302 G24303	\$300
Traulsen & Co., Inc.	G24304P	G24304P	Full Size	8.3	G24305P G24307P	\$300
Traulsen & Co., Inc.	G24310	G24310	Full Size	8.3	G24312 G24313	\$300
Traulsen & Co., Inc.	G24314P	G24314P	Full Size	8.3	G24315P G24317P	\$300

Note: Data based on applying ASTM F2140
N/A = Data Not Available

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Traulsen & Co., Inc.	RHF132W-FHS	RHF132W-FHS	Full Size	6.7	-	\$300
Traulsen & Co., Inc.	RHF132W-HHS	RHF132W-HHS	Full Size	6.7	-	\$300
Traulsen & Co., Inc.	RHF132WP-FHS	RHF132WP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF132WP-HHS	RHF132WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF232W-FHS	RHF232W-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF232W-HHS	RHF232W-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF232WP-FHS	RHF232WP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF232WP-HHS	RHF232WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF332W-FHS	RHF332W-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF332W-HHS	RHF332W-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF332WP-FHS	RHF332WP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RHF332WP-HHS	RHF332WP-HHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RIH132L-FHS	RIH132L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RIH132LP-FHS	RIH132LP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RIH232L-FHS	RIH232L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RIH232LP-FHS	RIH232LP-FHS	Full Size	6.3	-	\$300
Traulsen & Co., Inc.	RIH332L-FHS	RIH332L-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	RIH332LP-FHS	RIH332LP-FHS	Full Size	6.8	-	\$300
Traulsen & Co., Inc.	TB-150	TB-150	Full Size	16.0	-	\$300
Traulsen & Co., Inc.	TB-150FA	TB-150FA	Full Size	18.3	-	\$300
Traulsen & Co., Inc.	TB-90	TB-90	Full Size	10.7	TB-90FA	\$300
Traulsen & Co., Inc.	TB-96	TB-96	Full Size	10.3	TB-96FA	\$300
Traulsen & Co., Inc.	TSP-13	TSP-13	Full Size	9.7	TSP-13FA	\$300
Traulsen & Co., Inc.	TSP-15	TSP-15	Full Size	19.1	TSP-15S TSP-15FA TSP-15FS	\$300

Note: Data based on applying ASTM F2140
N/A = Data Not Available

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Vulcan	Holding and Transport Cabinet	VB150	Full Size	16.0	-	\$300
Vulcan	Holding and Transport Cabinet	VB90	Full Size	10.7	-	\$300
Vulcan	Holding and Transport Cabinet	VB96	Full Size	10.3	-	\$300
Vulcan	Holding and Transport Cabinet	VBP15I	Full Size	16.3	-	\$300
Vulcan	VBPFA15	VBPFA15	Full Size	19.1	VSCHFA15	\$300
Vulcan	HumidiHeat Humidified Holding & Transport Cabinet	VHMD13	Full Size	11.8	VHMD15	\$300
Vulcan	VHPFA7	VHPFA7	Full Size	19.5	-	\$300
Winston Industries	HA3022	HA3022GE	Full Size	15.7	-	\$300
Winston Industries	HA4522	HA4522GE	Full Size	19.1	HA4522Z	\$300
Winston Industries	HL4022	HL4022	Full Size	16.6	-	\$300
Winston Industries	HL4522	HL4522	Full Size	17.2	-	\$300
Wittco Foodservice Equipment	1220-7-FA	1220-7-FA	Full Size	19.5	-	\$300
Wittco Foodservice Equipment	Holding and Transport Cabinet	18 26-15-BC-IS	Full Size	13.4	18 26-15-SCH	\$300
Wittco Foodservice Equipment	Holding and Transport Cabinet	1826-13-HMD	Full Size	11.8	18-26-5-HMD 1826-15-HMD	\$300
Wittco Foodservice Equipment	1826-15-FA	1826-15-FA	Full Size	19.1	1826-15-SCH-FA	\$300

Note: Data based on applying ASTM F2140

N/A = Data Not Available

Qualified Insulated Holding Cabinets

Updated 5/11/2012

This measure does not include cook and hold equipment. All measures must be electric hot food holding cabinets that are fully insulated and have solid doors. Qualifying cabinets must not exceed the maximum idle energy rate of 20 Watts per cubic foot in accordance with the ASTM Standard F2140 test method. Check your utility rebate application for terms and conditions, and effective program dates.

Company Name	Model Name	Model Number	Size	Idle Energy Rate (Watts/ft ³)	Additional Models Represented	Rebate (per unit)
Wittco Foodservice Equipment	Banquet Cart	2-150	Full Size	16.0	-	\$300
Wittco Foodservice Equipment	Banquet Cart	2-90	Full Size	10.7	-	\$300
Wittco Foodservice Equipment	Banquet Cart	2-96	Full Size	10.3	-	\$300

Note: Data based on applying ASTM F2140
N/A = Data Not Available